

# INSTALLATION INSTRUCTIONS

ITEM REFERENCE NUMBER: TOB 4342

1. Carefully remove all parts from the carton.
2. Loosen thumbscrew (F) from fixture base (D) and open the shade cover (E).
3. Remove mounting plate (A) from fixture base (D) by removing cap nuts (C).
4. Affix mounting plate (A) to wall outlet box, and secure with mounting screws (B) provided.
5. Attach ground (green) wire to ground wire from wall outlet box (usually green or copper in color), fasten together with a plastic wire connector. Tightly wrap the wire connector with electrical tape so the end of the connector is sealed. **IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE PROPERLY GROUNDED.**
6. Connect both neutral (white) fixture wires coming from fixture base to neutral (usually white) outlet wire. Fasten both wires together with a plastic wire connector and tightly wrap the wire connector with electrical tape.
7. Repeat the procedure with the hot (black) wires. Always make sure that no wire strands are left outside the connectors. **DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OTHERWISE SAFETY WILL BE COMPROMISED.**
8. Remove metal tabs (H) by unscrewing set screws (G).
9. Place glass diffuser (J) to shade cover (E) and secure with metal tabs (H) and set screws (G).
10. Insert light bulb Type A, maximum 60 watt into the socket.
11. Attach fixture base (D) to affixed mounting plate (A), letting rods on mounting plate (A) pass through the holes on fixture base (D) and secure with cap nuts (C).
12. Close shade cover (E) to fixture base (D) and lock with thumbscrew (F).
13. Restore power and test fixture.

